

トロイダルコアの最大巻数表

単層巻最大巻数表																		
サイズ(AWG)			40	38	36	34	32	30	28	26	24	22	20	18	16	14	12	10
抵抗率(mΩ/cm)			35.4	21.3	13.6	8.57	5.32	3.40	2.13	1.34	0.842	0.530	0.330	0.210	0.132	0.083	0.052	0.033
品番	外周	表面積	巻数															
	cm	cm ²																
T5	0.197	0.089	12	8	6	4	2											
T7	0.249	0.154	20	15	11	8	5	3	2									
T10	0.295	0.248	28	21	16	12	8	6	4	2								
T12	0.428	0.445	43	33	26	20	15	11	8	5	3	1						
T12B	0.387	0.415	43	33	26	20	15	11	8	5	3	1						
T16	0.528	0.800	48	37	29	22	17	13	9	6	4	2	1					
T20	0.660	1.160	57	44	34	27	20	15	11	8	5	3	2	1				
T22	1.08	1.840	64	50	35	31	23	18	13	10	7	4	2	1				
T25	0.86	1.880	84	65	52	41	31	24	18	14	10	7	5	3	1			
T27	1.01	2.460	110	86	69	54	42	33	25	20	15	11	7	5	3	1		
T30	1.08	2.790	110	86	69	54	42	33	25	20	15	11	7	5	3	1		
T37	1.12	3.770	156	122	98	78	60	48	37	29	22	17	12	9	6	4	2	1
T44	1.39	5.230	177	138	111	88	69	55	43	34	26	20	15	11	7	5	3	1
T44A	1.23	4.800	177	138	111	88	69	55	43	34	26	20	15	11	7	5	3	1
T50	1.51	6.860	239	187	151	121	94	76	59	47	37	28	22	16	12	8	6	3
T51B	2.42	8.440	152	118	95	76	59	47	36	28	22	16	12	9	6	4	2	
T60	1.92	9.840	267	209	169	135	106	85	67	53	41	32	25	19	14	10	7	4
T68	1.83	11.200	296	232	187	150	117	94	74	59	46	36	28	21	16	12	8	5
T68A	2.15	12.500	296	232	187	150	117	94	74	59	46	36	28	21	16	12	8	5
T72	2.52	13.300	220	172	138	110	86	69	54	43	33	26	19	14	11	7	5	3
T80	2.10	15.500	402	316	255	204	161	129	103	82	64	51	39	30	23	17	13	9
T80B	2.75	18.700	402	316	255	204	161	129	103	82	64	51	39	30	23	17	13	9
T94	2.64	22.000	458	359	290	233	183	148	117	94	74	58	45	35	27	21	15	11
T106	3.57	31.000	462	362	293	235	185	149	118	95	74	59	46	36	27	21	15	11
T130	3.65	42.200	640	503	406	326	257	208	165	133	105	83	65	51	40	31	23	17
T157	4.62	63.200	784	616	499	401	316	256	204	164	129	103	81	64	50	39	30	23
T175	5.19	79.100	886	697	564	455	357	289	230	186	147	117	92	73	57	44	34	26
T184	6.04	89.200	780	613	496	398	314	254	202	163	129	102	81	63	50	38	29	22
T200	4.85	90.900	1035	814	658	529	418	338	270	217	172	137	108	86	67	53	41	31
T200B	7.19	120.000	1035	814	658	529	418	338	270	217	172	137	108	86	67	53	41	31
T225	5.11	109.000	1167	917	742	597	471	382	305	245	195	155	123	97	76	60	46	36
T225B	7.46	145.000	1167	917	742	597	471	382	305	245	195	155	123	97	76	60	46	36
T300	5.53	173.000	1612	1268	1027	826	653	529	422	341	271	216	171	136	108	85	66	52
T300D	8.14	223.000	1612	1268	1027	826	653	529	422	341	271	216	171	136	108	85	66	52
T400	8.02	301.000	1884	1482	1200	966	763	619	494	399	317	254	201	160	126	100	78	61
T400D	11.5	384.000	1884	1482	1200	966	763	619	494	399	317	254	201	160	126	100	78	61
T520	9.73	629.000	2589	2037	1650	1328	1050	852	680	550	437	350	278	221	176	139	109	86